



Vertical combination crusher: Our crushers are ideally suitable for primary and secondary crushing, with low power consumption and easy maintenance. Every feature of these machines has been carefully designed to provide superior quality and performance. They are widely used for crushing various materials like stone, granite, trap rock, coke, coal, manganese ore, iron ore, emery, fused aluminum, oxide, fused calcium carbide, lime stone, quartzite, alloys, etc. These crushers are recommended by leading consultants in this field and are used by hundreds of customers all over the world.



Technical parameters of Combination crusher

Model		800	1000	1250	1500	1750
Rotor diameter(mm)		650	800	1000	1250	1560
Cylinder height(mm)		800	850	850	1000	1410
Main shaft Rotation speed(Rotation/min)		1350	970	740	650	600
Feeding size(mm)		50	70	100	100	100
Discharging size(mm)		0-5	0-5	0-5	0-5	0-5
Processing capacity(t/h)		5-15	10-30	20-60	30-80	40-100
Motor	Power(kw)	30	55	75	110	132
	Rotation speed	1440	1440	750	750	750
Dimensions(L*W*H)(mm)		2200*860*1980	2700*1160*2000	2800*1400*2730	3100*1900*2300	3350*2100*2800
Weight(t)		2.3	4.5	9.73	18.1	26.61